FIG. 1A

DYNAMICALLY ADJUSTABLE DIGITAL GYRATOR HAVING EXTENDED FEEDBACK



FIG. 1B



FIG. 2A



50-ICO*RCO=ICO*RP=VP
ICO=14.27 mA
VP=35.7 Volts
Note: All results are at steady state

FIG. 2B

DYNAMICALLY ADJUSTABLE DIGITAL GYRATOR EXAMPLE



RP=Gyrator Impedance=400 ohms
RCO=Central Office Resistance

FIG. 3A

CODEC and Telephone System Stability Block Diagram



FIG. 3B



FIG. 4

Simplified D/A Path



FIG. 5A

DSP Based Gyrator Block Diagram



FIG. 5B



FIG. 6



FIG. 7A



FIG. 7B

10 Hz Fast DC Loop Filter Gain and Phase



FIG. 8A



FIG. 8B

1 Hz Slow DC Loop Filter Gain and Phase



FIG. 9

First Order Filter Topology



FIG. 10

Final Low Pass Topology with glitch removed





FIG. 11A

DC Loop Filter Without Hysterysis

FIG. 11B

DC Loop Filter With Hysterysis



FIG. 12A



FIG. 12B

TAS, PBX and Real Phone Line V/I Loadlines



FIG. 13A



FIG. 13B

TAS Termination with Lowpass Filter Cutoff = 1 Hz





FIG. 14A

FIG. 14B

TAS Termination with Lowpass Filter Cutoff = .1 Hz



FIG. 15
PRIOR ART



FIG. 16
PRIOR ART



FIG. 17
PRIOR ART



FIG. 18A
PRIOR ART



50-ICO*RCO=ICO*RP=VTIP
ICO=14.27 mA
VP=35.7 Volts
Note: All results are at steady state

FIG. 18B
PRIOR ART



LS=Gyrator Slow Charge Inductor
LF=Gyrator Fast Charge Inductor
RP=Gyrator Impedance
CAC=AC coupling capacitor for AC modem signals
RCO=Central Office Resistance